

Thermal Resistance	Minimum Thickness (inches)	Density of Insulation (lb/cu³)	Maximum Coverage (ft²/bag)	Minimum Weight (lb/ft²)
To obtain insulation resistance of:	Installed insulation shall not be less than:	Installed insulation shall not be less than:	Contents of the bag shall not cover more than:	Weight should not be less than:
34	9.25	0.8	51.1	0.617
35	9.25	0.9	45.4	0.694
36	9.25	1.0	40.9	0.771
34	9.5	0.8	49.7	0.633
36	9.5	0.9	44.2	0.713
37	9.5	1.0	39.8	0.792
41	11.25	0.8	42.0	0.750
42	11.25	0.9	37.3	0.844
44	11.25	1.1	30.5	1.031
43	11.875	0.8	39.8	0.792
44	11.875	0.9	35.4	0.891
46	11.875	1.0	31.8	0.990
43	12	0.8	39.4	0.800
45	12	0.9	35.0	0.900
46	12	1.0	31.5	1.000
51	14	0.8	33.8	0.933
52	14	0.9	30.0	1.050
54	14	1.0	27.0	1.167
58	16	0.8	29.5	1.067
60	16	0.9	26.3	1.200
62	16	1.0	23.6	1.333
65	18	0.8	26.3	1.200
67	18	0.9	23.3	1.350
69	18	1.0	21.0	1.500
72	20	0.8	23.6	1.333
75	20	0.9	21.0	1.500
77	20	1.0	18.9	1.667
80	22	0.8	21.5	1.467
82	22	0.9	19.1	1.650
85	22	1.0	17.2	1.833
87	24	0.8	19.7	1.600
90	24	0.9	17.5	1.800
92	24	1.0	15.8	2.000
100	26	1.0	14.5	2.167
104	26	1.2	12.1	2.600
109	26	1.5	9.7	3.250
108	28	1.0	13.5	2.333
112	28	1.2	11.3	2.800
117	28	1.5	9.0	3.500
115	30	1.0	12.6	2.500
120	30	1.2	10.5	3.000
125	30	1.5	8.4	3.750
123	32	1.0	11.8	2.667
128	32	1.2	9.8	3.200
133	32	1.5	7.9	4.000
131	34	1.0	11.1	2.833
136	34	1.2	9.3	3.400
142	34	1.5	7.4	4.250
139	36	1.0	10.5	3.000
144	36	1.2	8.8	3.600
150	36	1.5	7.0	4.500