



**ANY JOB.  
ANY SIZE.  
ANY PLACE.**

*55 Years of American Ingenuity*

## 2300

The **2300** is specifically designed for contractors, capable of blowing all brands of cellulose and fiberglass to manufacturer's specifications.

- Engineered for cellulose & fiberglass blowing insulation
- User friendly electric dashboard
- Clear acrylic safety gaurd allows for easy inspection
- Durable powder coat finish
- Built in tool holder
- All-fiber airlock machine
- Large hopper capacity for less reloading time
- Convertible fold down loading door

Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**

KRENDL MACHINE COMPANY • 1201 SPENCERVILLE AVE • DELPHOS, OHIO 45833 • 419.692.3060

[KrendlMachine.com](http://KrendlMachine.com)

# 2300

## MATERIAL PRODUCTION RATE

MATERIAL	lbs/hr (kg/hr)
<b>FIBERGLASS</b>	<b>1000 (454)</b>
<b>CELLULOSE</b>	<b>3000 (1360)</b>

lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.)  
Hose at 16 ft. (4.8 m.) elevation, product brand, product density  
and variable blowing conditions will affect production rate.

### • POWER REQUIREMENT •

Double input, 30/20 amps each/120 volt/60hz  
Single input, 30 amp 240volt/60hz  
International -Double input, 230volt/50hz  
CE/CSA/CUL /UL

### • HOPPER CAPACITY •

40 cu. ft. (1.13 m<sup>3</sup>)  
Loading made easy with built in  
convertible tray

### • WEIGHT/DIMENSIONS •

846 lbs / 32"W x 62"D x 68"H  
384 kg. / 81cm x 157cm x 173cm

### • BLOWER/SIZE •

14 amp/2-stage (120 volt)  
Double Blower System yields  
140 CFM @ 3 1/2 PSI per blower

### Dual Agitators

Designed for Constant Flow



Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**

## Electric Dashboard

- LED start & stop buttons • Digital hourmeter
- Digital voltmeter • Dual variable blower controls
- Recessed power supply



**2 HP Direct Drive Motor/Reducer**  
w/overload protection of transformer



**Double Blower System**  
14 amp/2-stage (120 volt)



**Slideout Airlock System**  
16" x 12" diameter  
(40.6cm. x 30.5cm. diameter)  
3" (7.6cm.) Outlet



**Clear Acrylic Safety Guard**  
Allows for Inspection

