



**ANY JOB.
ANY SIZE.
ANY PLACE.**

55 Years of American Ingenuity

2800-G

The **2800-G** is specifically designed for contractors to provide a smaller designed footprint while capable of blowing all brands of cellulose and fiberglass.

- 18 Hp Briggs & Stratton V-Twin gas engine w/positive pressure lubrication system
- Removable all steel airlock allows quick access for maintenance
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Convertible fold down loading door
- Engineered for cellulose & fiberglass blowing insulation
- User friendly 12 VDC electric dashboard
- Control panel with engine controls, pressure gauge and air bleed off
- 5 plus gallon fuel tank w/emergency shut off
- Clear acrylic safety guard allows for easy inspection

Backed by a manufacturer's
2-YEAR WARRANTY - Made in the U.S.A.

2800-G

MATERIAL PRODUCTION RATE

MATERIAL	lbs/hr (kg/hr)
FIBERGLASS	2100 (953)
CELLULOSE	3600 (1633)

lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.) Hose at 16 ft. (4.8 m.) elevation, product brand, product density and variable blowing conditions will affect production rate.

• HOPPER CAPACITY •

40 cu. ft. (1.13 m³)

Loading made easy with built in convertible tray

• WEIGHT/DIMENSIONS •

1224 lbs / 39"W x 68 1/2"D x 73"H

555 kg. / 99cm x 174cm x 185cm

• BLOWER/SIZE •

Positive Displacement Blower
Blower System yields
135 CFM @ 6 PSI



18 HP Briggs & Stratton V-Twin Gas Engine

w/positive pressure lubrication system



Positive Displacement Blower

w/135 CFM @ 6 psi



Control Panel

w/engine controls, pressure gauge
and air bleed off



Slideout Airlock System

16" x 12" diameter
(40.6cm. x 30.4cm. diameter)
3" (7.6cm.) Outlet

12 VDC Electric Dashboard

w/LED start & stop buttons



Dual Agitators

Designed for Constant Flow



Backed by a manufacturer's
2-YEAR WARRANTY - Made in the U.S.A.

