

Polyguard® Airlok Flex®

Fluid-Applied / Air Barrier Membrane

MATERIALS LIST

ABOVE-GRADE FLUID-APPLIED AIR BARRIER

Polyguard Airlok Flex®

Airlok Flex® is a fluid-applied air barrier coating and is used over CMU and gypsum sheathing. It is not recommended for use on wood substrates. It can be applied in temperatures between -20°F (-29°C) to 120°F (49°C), at an application thickness of 40 mils wet, and a coverage rate of 40 SF per gallon. It is available in VOC formulations for 525, 400, 200 and 100. It is UV resistant up to 6 months.

| Polyguard Airlok Flex® | Part Number | Unit Size | Units/pallet | Wt/unit |
|--|-------------------------------|---|---------------------|----------------|
| <i>Proban® mold inhibitor can be added at the factory to Airlok Flex®</i> | PWALFLEX GRAY 05 | 5 gallon pail | 36 pails/pallet | 43#/pail |
| | PWALFLEX GRAY 55 | 55 gallon drum | 4 dr/pallet | 450#/dr |
| Polyguard Airlok Flex® Accessories: | Part Number | Unit Size | Units/pallet | Wt/unit |
| Detail Sealant PW™ 20 oz. sausage | DETAIL SEALANT PW – SAU 20 OZ | 20 sausages/ctn | 45 ctns/pallet | 45#/ctn |
| Detail Sealant PW™ 3 gal. pail | DETAIL SEALANT PW – 3 GAL | 3 gallon pail | 36 pails/pallet | 37#/pail |
| 400 Flashing - 40 mil (sizes available: 4", 6", 9", 12", 16", 24") | varies/size | 75' roll | varies/size | varies/size |
| 400 Membrane - 40 mil (48") | varies/size | 48" x 75' roll | 25 ctns/pallet | 76#/ctn |
| Aluma Flash™ / Peel 'N Stick™ 4", 6", 9", 12", 18", 36") | varies/size | 33.3' roll | 42 ctns/pallet | 37#/ctn |
| Polyguard 650 LT Liquid Adhesive or Shur-Tac Liquid Adhesive are not required as a primer when Aluma Flash or 400 Membranes are applied over cured Airlok Flex®. | | | | |
| Quick Grip Spray Adhesive | PWQGADH30 | 30# canister covers approximately 1000 SF | | |