

Polyguard® Commercial Stretch

Fluid-Applied Waterproofing Membrane

MATERIALS LIST

BELOW-GRADE FLUID-APPLIED WATERPROOFING

Polyguard Commercial Stretch®

Commercial Stretch is a fluid-applied coating used primarily to waterproof below-grade walls. It can be applied in temperatures between -20°F (-29°C) to 120°F (49°C), at an application thickness of 60 mils wet, and a coverage rate of 27 SF per gallon. It is available in gray (standard color) and beige (special order only). It is available in VOC formulations for 525, 400, 200 and 100.

Polyguard Commercial Stretch <i>Proban® mold inhibitor can be added at the factory to Commercial Stretch</i>	Part Number	Unit Size	Units/pallet	Wt/unit
	PWSTRETCH GRAY 05	5 gallon pail	36 pails/pallet	48#/pail
	PWSTRETCH GRAY 55	55 gallon drum	4 dr/pallet	520#/dr
Polyguard Commercial Stretch Accessories:	Part Number	Unit Size	Units/pallet	Wt/unit
Detail Sealant PW™ 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Detail Sealant PW™ 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3 gallon pail	36 pails/pallet	37#/pail
Lowflow™	LOWF	4' x 200' roll	9 rolls/pallet	100#/roll
Polyflow® 10	POLYFLOW10	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 10P	POLYFLOW10P	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 15	POLYFLOW15	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 15P	POLYFLOW15	4' x 50' roll	8 rolls/pallet	43#/roll
Totalflow™	TOTAL FLOW	24" x 50' roll	12 rolls/pallet	30#/roll
Totalflow™ End Outlet (4")	OUTLET4-UNIV	N/A	N/A	N/A
Totalflow™ Tee Outlet (4")	TEE4-UNIV	N/A	N/A	N/A
Quick Grip Spray Adhesive	PWQGADH30	30# canister covers approximately 1000 SF		