

# Polyguard® PRO 1000

## Fluid-Applied Dampproofing Membrane

### MATERIALS LIST

<b>BELOW-GRADE FLUID-APPLIED DAMPPROOFING</b>				
<b>Polyguard PRO 1000</b>				
PRO 1000 is a fluid-applied coating used primarily to dampproof below-grade walls. It can be applied in temperatures between -20°F (-29°C) to 120°F (49°C), at an application thickness of 40 mils wet, and a coverage rate of 40 SF per gallon.				
<b>Polyguard PRO 1000</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
<i>Proban® mold inhibitor can be added at the factory to Pro 1000</i>	PWPRO1000 GRAY 05	5 gallon pail	36 pails/pallet	48#/pail
	PWPRO1000 GRAY 55	55 gallon drum	4 dr/pallet	520#/dr
<b>Polyguard PRO 1000 Accessories:</b>	<b>Part Number</b>	<b>Unit Size</b>	<b>Units/pallet</b>	<b>Wt/unit</b>
Detail Sealant PW™ 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Detail Sealant PW™ 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3 gallon pail	36 pails/pallet	37#/pail
Lowflow™	LOWF	4' x 200' roll	9 rolls/pallet	100#/roll
Polyflow® 10	POLYFLOW10	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 10P	POLYFLOW10P	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 15	POLYFLOW15	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 15P	POLYFLOW15P	4' x 50' roll	8 rolls/pallet	43#/roll
Polyflow® 18	POLYFLOW18	4' x 50' roll	8 rolls/pallet	45#/roll
Totalflow™	TOTAL FLOW	24" x 50' roll	12 rolls/pallet	30#/roll
Totalflow™ End Outlet (4")	OUTLET4-UNIV	N/A	N/A	N/A
Totalflow™ Tee Outlet (4")	TEE4-UNIV	N/A	N/A	N/A
Quick Grip Spray Adhesive	PWQGADH30	30# canister covers approximately 1000 SF		